



Monoblock

PUMPS

Monoblock

PUMPS

ikuh dh /kkj
yxkkrkj----

ikuh dh /kkj
yxkkrkj----



An ISO 9001:2008 Certified Company



An ISO 9001:2008 Certified Company

igys ls csgrj vkSj ls T;knk xkjU

igys ls csgrj vkSj ls T;knk xkjU

THUNDER

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.1 H.P. / 0.8 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 5.5A
Size : 25mm x 25mm
Total Head : 48 Mtrs.



TURBO

1 HP TURBO

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 5.5A
Size : 25mm x 25mm
Total Head : 37 Mtrs.



EXTRA FLOW

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1 & 1.5 H.P.
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A & 10A.
Size : 25mm x 25mm
Total Head : 50 & 60 Mtrs.




EXTRA FLOW

0.5 HP & 1 HP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 0.5, 1 H.P.
Speed : 2900 R.P.M.
Duty : Continuous
Max. Current : 3A /6A
Size : 25mm x 25mm
Total Head : 30 Mtrs. / 50 Mtrs.



SHALLOW-WELL

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A
Size : 25mm x 25mm
Total Head : 37 Mtrs.



Pressure Booster

SPECIFICATIONS

Motor Rating : 1.0 H.P. / 0.75KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A
Size : 25mm x 25mm
Total Head : 45 Mtrs.



Exclusive for Jacuzzi & Pressure.

SEWAGE DRAIN PUMP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Total Head : 7 Mtr.
Duty : 2.7A
Size : 25mm X 25mm



Exclusive for Drain in Kitchen & Basement.

TRENDY

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2900 R.P.M.
Duty : Continuous
Max. Current : 7A
Size : 25mm x 25mm
Total Head : 50Mtrs.



BOREWELL SUBMERSIBLE PUMP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. To 3.0 HP
Speed : 2900 R.P.M.
Duty : Continuous
Size : 32.50,
Total Head : 3 Mtrs. To 170 Mtrs.



COOLER PUMP

SPECIFICATIONS

Supply : AC 220V, 50Hz
Power : 150W
Max. Flow : 3900 Lph
Max. Head : 5/8 Ft.
For outdoor fountains/water cascades as well as commercial desert cooler. Also used for de-watering of tanks (clean water only-fresh as well as saline)



THUNDER

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.1 H.P. / 0.8 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 5.5A
Size : 25mm x 25mm
Total Head : 48 Mtrs.



TURBO

1 HP TURBO

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 5.5A
Size : 25mm x 25mm
Total Head : 37 Mtrs.



EXTRA FLOW

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1 & 1.5 H.P.
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A & 10A.
Size : 25mm x 25mm
Total Head : 50 & 60 Mtrs.



EXTRA FLOW

0.5 HP & 1 HP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 0.5, 1 H.P.
Speed : 2900 R.P.M.
Duty : Continuous
Max. Current : 3A /6A
Size : 25mm x 25mm
Total Head : 30 Mtrs. / 50 Mtrs.



SHALLOW-WELL

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A
Size : 25mm x 25mm
Total Head : 37 Mtrs.



Pressure Booster

SPECIFICATIONS

Motor Rating : 1.0 H.P. / 0.75KW
Speed : 2800 R.P.M.
Duty : Continuous
Max. Current : 6A
Size : 25mm x 25mm
Total Head : 45 Mtrs.



Exclusive for Jacuzzi & Pressure.

SEWAGE DRAIN PUMP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Total Head : 7 Mtr.
Duty : 2.7A
Size : 25mm X 25mm



Exclusive for Drain in Kitchen & Basement.

TRENDY

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. / 0.75 KW
Speed : 2900 R.P.M.
Duty : Continuous
Max. Current : 7A
Size : 25mm x 25mm
Total Head : 50Mtrs.



BOREWELL SUBMERSIBLE PUMP

SPECIFICATIONS

Supply : 220V / 50 Hz, Single Phase
Motor Rating : 1.0 H.P. To 3.0 HP
Speed : 2900 R.P.M.
Duty : Continuous
Size : 32.50,
Total Head : 3 Mtrs. To 170 Mtrs.



COOLER PUMP

SPECIFICATIONS

Supply : AC 220V, 50Hz
Power : 150W
Max. Flow : 3900 Lph
Max. Head : 5/8 Ft.
For outdoor fountains/water cascades as well as commercial desert cooler. Also used for de-watering of tanks (clean water only-fresh as well as saline)



GRIPPER 63 MM WORK & TUMBLE